

Alba Racing Yamaha YXZ1000 R/SS Spark Arrestor Installation

Tools Required:

3/8" drive torque wrench

3/8" drive ratchet

3/8" drive extension 10" long

3/8" drive swivel extension

8mm socket

5mm Allen wrench or socket



It is always best to lay out your tools and parts in an organized fashion. Always allow ample time for the exhaust to cool before beginning. Failure to allow exhaust to cool can cause serious burns. If you have questions regarding this install please contact Alba Racing prior to attempting to install at 619-562-0188.

1. You will be replacing the spark arrestor behind the OEM muffler end cap.



2. Begin by using the 5mm Allen wrench or Allen socket and ratchet to remove the muffler end cap retaining bolts.



3. Carefully remove the muffler end cap.



4. Using the 8mm socket, 3/8" drive swivel extension, 10" extension, and 3/8" drive ratchet carefully remove the six 8mm spark arrestor retaining bolts. These bolts have been known to break easily so take your time here. Some WD-40 may help.

5. Remove the OEM spark arrestor making sure to get the gasket as well.



6. Move the OEM gasket over to the new Alba Racing Spark Arrestor and with 2 bolts in place install it into the back of the muffler loosely. Using 2 bolts will help keep the gasket in place while positioning.



7. Loosely install and snug all remaining 8mm retaining bolts.



8. Using torque wrench torque 8mm retaining bolts to 7.2 ft/lbs.

9. Install factory muffler end cap and tight 5mm Allen wrench muffler end cap retaining bolts to 5.8 ft/lbs.





You have now completed the installation of the Alba
Racing Spark Arrestor. Enjoy your new found power!!!