

## Alba Racing Yamaha YXZ1000 R/SS SBD Header Installation

Tools required:

3/8" drive torque wrench

3/8" drive ratchet

3/8" drive extension 10" long

3/8" drive swivel extension

12mm deep socket

10mm deep or shallow socket



It is always best to lay out your tools and parts in an organized fashion. Always allow ample time for the exhaust to cool before beginning. Failure to allow exhaust to cool can cause serious burns. If you have questions regarding this install please contact Alba Racing prior to attempting to install at 619-562-0188.

1. Using the 12mm deep socket, extension, and ratchet remove the six 12mm nuts retaining the stock header. You will be re-using these nuts.



2. Using the 10mm socket and 3/8" ratchet loosen the header to muffler retaining clamp bolt. You will be re-using this clamp.



3. Pull towards your body to remove the stock header.



4. You should now have no header on the vehicle like in the following picture.





5. Install the new Alba Racing SBD Header. You may need to wiggle the header a bit to get it seated into the head and muffler.



6. Loosely re-install the six 12mm nuts. **DO NOT TIGHTEN THEM YET.**



7. Loosely re-install the 10mm retaining clamp bolt.



8. Now that everything is loosely tightened go back to the six 12mm header bolts and using the 3/8" torque wrench tighten them to 14 ft/lbs.
9. Next tighten the 10mm retaining clamp bolt using the torque wrench to 14 ft/lbs also.
10. Clean off any grease or finger prints before starting.

You have now completed the installation of the Alba Racing SBD Header. Enjoy your new found power!!!