



Alba Racing LT-R450 Nerf Bar Installation

Pic 1:



Step 1 – (Refer to picture #1) Find the two chrome mount tubes, the two aluminum spacers and the two 70mm long bolts. These are used to mount the front tube of the nerf to the bottom bolt of the lower front engine mount. Using a #12 socket remove this bolt from the lower front engine mount (it is where the bracket gets bolted to the frame). Next, grab one of the chrome mounts. Put the bolt thru the hole on the tab, and then put the spacer on the bolt. Screw the bolt into the engine mount hole. Do not tighten this bolt yet, just snug it up. When you mount the brake side please make sure to put the wire that runs down the frame over the spacer being careful not to pinch it.

Pic 2:



ALBA RACING

Step 2 – (refer to picture #2) Take the shifter side nerf bar and slide the front tube on the tube of the mount just installed. Use the 20mm long bolts to mount the nerf bar tab to the foot peg. Insert the bolts thru the mount tab holes, and then thru the holes in the foot peg. Install a washer and a nylok nut. Tighten the nuts being sure that the top of the nerf mount tab is parallel to the teeth on the foot peg. Repeat this process for the brake side. Now tighten the bolt on the front mount.

Pic 3:



Step 3 – (refer to picture #3) install the nets following the diagram.

Step 4 – Check all 6 bolts and nuts for tightness. It is also a good plan to recheck all bolts and nuts for tightness after you ride the quad.

Finished Install:



Care – Your Alba nerf bars are polished then anodized to allow low maintenance use. Use soap and water to clean them. Do not use abrasive cleaners such as aluminum polish as it will scratch or dull the finish. Try to avoid stepping on them as this may scratch the finish.